



AVC708H

16CH All-in-One DVR



 **PUSH VIDEO**

**Push Video + EagleEyes + Full D1 +
1080P HDMI + IVA + DCCS +
960H Video Recording**

FEATURES

Push Video - Active Event Notification with EagleEyes App

- ✓ Supports sending Push Video to your iPad, iPhone and Android mobile device for instant event notification for an alarm event when a human detection camera or an alarm sensor is connected to the DVR.

Mobile Surveillance with EagleEyes App

- ✓ Compatible with many popular mobile devices, such as iPhone, iPad, BlackBerry, Symbian, Windows Mobile & Android mobile devices.

Remote Surveillance with Browsers and CMS

- ✓ For web browsers, compatible with Internet Explorer, Mozilla Firefox, Google Chrome, Safari & Opera.
- ✓ For CMS software, available with our self-developed and free software, "Video Viewer."
- ✓ Applicable also to Apple's media player, QuickTime.

Video Output

- ✓ Full HD video display
- ✓ Dual video output for both VGA & HDMI

Intelligent Video Analysis

- ✓ Virtual Fence:
virtual intruder detection line is set to detect intruders crossing the detection line.
- ✓ Flow Counting:
virtual detection line is set to detect the moving direction of pedestrians for flow counting.
- ✓ Single Channel Motion Recording:
Only the channel with an event will be recorded to effectively save a significant amount of hard disk space and have the maximized recording time.

960H Video Recording

- ✓ Supports 960H image display for evidentiary recording with high quality and clear images.

Independent Channel Control

- ✓ Definable "Resolution" / "Quality" / "FPS" by channels at your preferences to increase the recording efficiency, and avoid any important scenes to be missed.

Remote Independent Operation

- ✓ Channel switching is independent from the local site, allowing users to have private image monitoring remotely.

Multiplex

- ✓ Allows live display, record, playback, backup and network operation at the same time.

Backup Function

- ✓ Supports USB flash drive and network backup.



SPECIFICATIONS

| q Video | | |
|--------------------------------|---|--|
| Video System | NTSC / PAL (auto detection) | |
| Video Compression Format | H.264 | |
| Video Input | 16 channels (Composite video signal 1 Vp-p 75Ω BNC) | |
| Video Loop Output | 16 channels (Composite video signal 1 Vp-p 75Ω BNC) | |
| Video Output | BNC | YES (Call monitor for sequence display) |
| | VGA | YES |
| | HDMI | YES (Full HD display) |
| Dual Video Output | YES | |
| q Record & Backup | | |
| Maximum Recording Rate | 960H | 960 x 480 pixels with 360 IPS <NTSC> / 960 x 576 pixels with 300 IPS <PAL> |
| | Frame | 704x480 pixels with 480 IPS <NTSC> / 704x576 pixels with 400 IPS <PAL> |
| | Field | 704x240 pixels with 480 IPS <NTSC> / 704x288 pixels with 400 IPS <PAL> |
| | CIF | 352x240 pixels with 480 IPS <NTSC> / 352x288 pixels with 400 IPS <PAL> |
| Recording Mode | Manual / Timer / Motion / Alarm / Remote | |
| Pre-alarm Recording | YES | |
| Quick Search | Time / Motion / Alarm search mode | |
| Backup Device | DVD Writer (Optional) / USB 2.0 flash drive / Network | |
| q Audio | | |
| Audio Input | 4 audio inputs | |
| Audio Output | 2 audio outputs (Mono) | |
| q General | | |
| Hard Disk Storage | Accommodates 2 SATA HDDs (1 HDD capacity up to 2TB) | |
| SATA Interface | YES | |
| eSATA Interface | YES (For external disk array connection) | |
| Image Quality Setting | SUPER BEST / BEST / HIGH / NORMAL | |
| USB Mouse Control | YES | |
| Motion Detection Area | 16 x 12 grids per channel | |
| Motion Detection Sensitivity | 3 adjustable parameters for accurate detection | |
| Event Notification | Push Video / FTP / E-Mail | |
| Picture Zoom | 2X digital zoom | |
| PTZ Control | YES | |
| Alarm I/O | 16 inputs (4 inputs for Push Video), 1 output | |
| IR Remote Control | YES (IR receiver built-in) | |
| Key Lock (Password Protection) | YES | |
| User Level | 4 user levels for different access privilege | |
| Video Loss Detection | YES | |
| Camera Title | Supports up to 12 letters | |
| Video Adjustable | Hue / Saturation / Contrast / Brightness | |
| Date Display Format | YY/MM/DD, DD/MM/YY & MM/DD/YY | |
| Daylight Saving | YES | |
| Power Source (±10%) | DC 19V | |
| Power Consumption (±10%) | < 64 W | |
| Operating Temperature | 10°C ~ 40°C (50°F ~104°F) | |
| Dimensions (mm)** | 432(W) x 90(H) x 326(D) | |
| q Network | | |
| Ethernet | 10/100 Base-T. Supports remote control and live view via Ethernet | |
| Network Protocol | TCP/IP, PPPOE, DHCP and DDNS | |



SPECIFICATIONS

| q Remote Surveillance from PC | |
|---|--|
| Compatible Operating System | Windows & MAC |
| Compatible Program | Web Browser: Internet Explorer, Mozilla Firefox, Google Chrome, Safari & Opera |
| | Video Viewer: For both Windows and MAC operating systems |
| | QuickTime For both Windows and MAC operating systems |
| Max. online users | 10 |
| Web Transmitting Compression Format | H.264 |
| Network Live Audio | YES |
| Remote Independent Operation | YES |
| Remote Event Download & Playback | YES |
| R.E.T.R. (Remote Event Trigger Recording) | YES |
| q Mobile Surveillance | |
| App | EagleEyes |
| Compatible Devices | iPad, iPhone, BlackBerry, Windows Mobile, Symbian & Android mobile devices |
| Push Video | YES (With EagleEyes for iPhone, iPad, Android versions) |
| q Others | |
| DCCS Support | YES (1 channel) |
| IVA Support | YES (4 channels) |
| AVTECH Free DDNS service | YES |
| Multiplex Operation | Live display / record / playback / backup / network operations |
| System Recovery | System auto recovery after power failure |
| Optional Peripherals | Keyboard Controller |

*The specifications are subject to change without notice.

** Dimensional tolerance: ±5mm

REAR PANEL

